




4332401000759



规格 Specifications

1. 减速比 Gear Ratio	20:1
2. 减速级数 Gear Stage	2
3. 回程间隙 Backlash	≤15arc-min
4. 转动惯量 Kgcm ² Moment of inertia	0.019 Kgcm ²
5. 额定扭矩 Rated output torque	20 NM
6. 瞬间承受最大扭矩 Instant stop torque	2倍于额定输出力矩 (two times of rated torque)
7. 传动效率 Full load efficiency	94%
8. 寿命 Life	20000 hour
9. 重量 Weight	0.5 KG
10. 保护等级 IP	IP54
11. 适配电机 Adapted motor	NEMA16,17 stepper motor

Unit: mm
 第一角画法
 FIRST ANGLE METHOD
 未注线性与角度尺寸公差
 Tolerances for linear and angular dimensions without individual tolerance indications
 GB/T 1804-m eqv ISO 2768-1: m
 未注形状与位置尺寸公差
 Geometrical tolerance for features without individual tolerance indications
 GB/T 1184-K eqv ISO 2768-2: K

批准 Approve		
标准化 Standard		
工艺 Technology		
审核 Check		
设计 Design	段伟	2019.12.18

MOONS'
 Shanghai Moons' Electric Co., Ltd.
 GEARBOX 减速机

This document is released for information only. Its reproduction in whole or in part or its dissemination to third parties is prohibited. All trademarks and registered trademarks appearing on this document are the property of their respective owners.

REV.	版本记录 REVISION RECORD	DATE	UNLESS OTHERWISE SPECIFIED	NAMES	SIGNATURE	DATE	40ZDE20-052210	REV. A	SCALE 1:1	Sheet 1 of 1
------	----------------------	------	----------------------------	-------	-----------	------	----------------	--------	-----------	--------------

1 2 3 4 5 6 7 8